according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

MIXOL® Nr. 4 Oxyd-Rot

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Colour, Pigment

## 1.3. Details of the supplier of the safety data sheet

Company name: MIXOL-PRODUKTE Diebold GmbH

Street: Carl-Zeiss-Str. 17-19
Place: D-73230 Kirchheim/Teck

Telephone: +49/(0)7021 / 950090 Telefax: +49/(0)7021 / 56030

E-mail: info@mixol.de
E-mail (Contact person): Technik@mixol.de
Internet: www.mixol.de
Responsible Department: Technik

1.4. Emergency telephone Emergency CONTACT (24 h) GBK GmbH +49/(0)6132 / 84463

number:

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

# 2.2. Label elements

### **GB CLP Regulation**

## Special labelling of certain mixtures

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5

-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce

an allergic reaction.

EUH210 Safety data sheet available on request.

# 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 2 of 13

## Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)		•		
68920-66-1	Alcohols, C16-18 and C18-unsatd.,	ethoxylated		5 - < 10 %	
	500-236-9				
	Acute Tox. 4, Skin Irrit. 2, Eye Dam H400 H412	. 1, Aquatic Acute 1, Aquatic Chronic	c 3; H302 H315 H318		
68920-66-1	Alcohols, C16-18 and C18-unsatd.,		1 - < 5 %		
	500-236-9				
	Skin Irrit. 2, Aquatic Acute 1, Aquat	ic Chronic 3; H315 H400 H412			
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			< 0.05 %	
	220-120-9	613-088-00-6	01-2120761540-60		
	Acute Tox. 2, Acute Tox. 4, Skin Irr Chronic 2; H330 H302 H315 H318	it. 2, Eye Dam. 1, Skin Sens. 1, Aqua H317 H400 H411	atic Acute 1, Aquatic		
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)			< 0.0015 %	
	-	613-167-00-5	01-2120764691-48		
	•	 Fox. 3, Skin Corr. 1C, Eye Dam. 1, Sl I310 H301 H314 H318 H317 H400 H	· · · · · · · · · · · · · · · · · · ·		

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
68920-66-1	500-236-9	Alcohols, C16-18 and C18-unsatd., ethoxylated	5 - < 10 %
	oral: ATE = 500	0 mg/kg Aquatic Acute 1; H400: M=1	
68920-66-1	500-236-9	Alcohols, C16-18 and C18-unsatd., ethoxylated	1 - < 5 %
	Aquatic Acute 1	; H400: M=1	
2634-33-5	220-120-9	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	< 0.05 %
		E = 0,5 mg/l (vapours); inhalation: LC50 = 0,5 mg/l (dusts or mists); dermal: LD50 ; oral: LD50 = 670 - 784 mg/kg	
55965-84-9			< 0.0015 %
	LD50 = 92,4 mg H315: >= 0,06 - Skin Sens. 1A; Aquatic Acute 1	E = 0,5 mg/l (vapours); inhalation: LC50 = 0,171 mg/l (dusts or mists); dermal: g/kg; oral: LD50 = 64 mg/kg	

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## **General information**

When in doubt or if symptoms are observed, get medical advice.

## After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Get medical advice/attention.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

according to UK REACH Regulation

## MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 3 of 13

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

### After ingestion

Observe risk of aspiration if vomiting occurs. @0405.B004145 Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Water spray jet, Extinguishing powder, Carbon dioxide (CO2), alcohol resistant foam.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Non-flammable. In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Nitrogen oxides (NOx).

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

## Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General advice

Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin, eyes and clothes.

### For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

### For emergency responders

Wear personal protection equipment (refer to section 8).

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### 6.3. Methods and material for containment and cleaning up

### For containment

Stop leak if safe to do so. Cover drains.

## For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 4 of 13

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation. Avoid contact with skin, eyes and clothes. Do not breathe dust/fume/gas/mist/vapours/spray. Use personal protection equipment.

## Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

## Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Wash hands before breaks and after work. Draw up and observe skin protection programme. Use protective skin cream before handling the product. When using do not eat, drink, smoke, sniff.

### Further information on handling

Handle and open container with care.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints on joint storage

No information available.

# Further information on storage conditions

storage stability: >= 36 month(s)

## 7.3. Specific end use(s)

Colour, Pigment

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1317-65-3	Calcium carbonate, respirable	-	4		TWA (8 h)	WEL
1309-37-1	Iron oxide, fume (as Fe)	-	5		TWA (8 h)	WEL
		-	10		STEL (15 min)	WEL
57-55-6	Propane-1,2-diol, particulates	-	10		TWA (8 h)	WEL
1309-37-1	Rouge, respirable	-	4		TWA (8 h)	WEL
1309-37-1	Rouge, total inhalable	-	10		TWA (8 h)	WEL
-	Silica, amorphous, inhalable dust	-	6		TWA (8 h)	WEL
-	Silica, amorphous, respirable dust	-	2.4		TWA (8 h)	WEL

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 5 of 13

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
57-55-6	Propane-1,2-diol			
Worker DNEL	long-term	inhalation	systemic	168 mg/m³
Worker DNEL	long-term	inhalation	local	10 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	50 mg/m³
Consumer DN	EL, long-term	inhalation	local	10 mg/m³
Consumer DN	EL, long-term	dermal	systemic	213 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	85 mg/kg bw/day
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one			
Worker DNEL	long-term	inhalation	systemic	6,81 mg/m³
Worker DNEL	long-term	dermal	systemic	0,966 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	1,2 mg/m³
Consumer DN	EL, long-term	dermal	systemic	0,345 mg/kg bw/day
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one	and 2-methyl-2H-isothi	azol-3-one (3:1)	
Worker DNEL	long-term	inhalation	local	0,02 mg/m³
Worker DNEL	acute	inhalation	local	0,04 mg/m³
Consumer DN	EL, long-term	inhalation	local	0,02 mg/m³
Consumer DNEL, acute		inhalation	local	0,04 mg/m³
Consumer DNEL, long-term		oral	systemic	0,09 mg/kg bw/day
Consumer DN	EL, acute	oral	systemic	0,11 mg/kg bw/day

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 6 of 13

### **PNEC values**

CAS No	Substance	
Environmental	compartment	Value
57-55-6	Propane-1,2-diol	<u> </u>
Freshwater	•	260 mg/l
Freshwater (in	termittent releases)	183 mg/l
Marine water		26 mg/l
Marine water (	intermittent releases)	183 mg/l
Freshwater se	diment	572 mg/kg
Marine sedime	ent	57,2 mg/kg
Micro-organisr	ns in sewage treatment plants (STP)	20000 mg/l
Soil		50 mg/kg
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	
Freshwater		0,00403 mg/l
Freshwater (in	termittent releases)	0,0011 mg/l
Marine water		0,000403 mg/l
Freshwater se	diment	0,0499 mg/kg
Marine sedime	ent	0,00499 mg/kg
Micro-organisr	ns in sewage treatment plants (STP)	1,03 mg/l
Soil		3 mg/kg
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	(3:1)
Freshwater		0,00339 mg/l
Freshwater (intermittent releases)		0,00339 mg/l
Marine water		0,00339 mg/l
Freshwater sediment 0		
Marine sediment 0,027 mg/kg		
Micro-organisr	ns in sewage treatment plants (STP)	0,23 mg/l
Soil		0,01 mg/kg

## 8.2. Exposure controls





# Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye protection/face protection.

# Hand protection

Wear protective gloves.

Suitable material: NBR (Nitrile rubber)

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

according to UK REACH Regulation

## MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 7 of 13

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Breakthrough times and swelling properties of the material must be taken into consideration.

### Skin protection

Use of protective clothing.

# **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

#### Thermal hazards

No information available.

### **Environmental exposure controls**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: Liquid (Dispersion)

Colour: red
Odour: odourless
Odour threshold: not applicable

Melting point/freezing point:

Boiling point or initial boiling point and

100 °C

boiling range:

Flammability: Non-flammable. Lower explosion limits: not determined Upper explosion limits: not determined Flash point: > 100 °C Auto-ignition temperature: not determined Decomposition temperature: > 100 °C pH-Value: not determined Viscosity / kinematic: not determined Water solubility: miscible

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

Particle characteristics:

not determined

not determined

not determined

not determined

not applicable

# 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 8 of 13

## 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide, Carbon dioxide (CO2), Nitrogen oxides (NOx).

## **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix:

oral: > 2000 mg/kg dermal: > 2000 mg/kg

Inhalation (vapour): >20 mg/L (4 h) Inhalation (dust/mist): > 5 mg/L (4h)

## **ATEmix** calculated

ATE (oral) 6676 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
68920-66-1	Alcohols, C16-18 and	C18-unsatd.,	ethoxylated				
	oral	ATE mg/kg	500				
2634-33-5	1,2-benzisothiazol-3(2l	H)-one; 1,2-b	enzisothiazolii	n-3-one			
	oral	LD50 mg/kg	670 - 784	Rat	Manufacturer	OECD 401	
	dermal	LD50 mg/kg	> 2000	Rat	Manufacturer	OECD 402	
	inhalation vapour	ATE	0,5 mg/l				
	inhalation (4 h) dust/mist	LC50	0,5 mg/l	Rat	Manufacturer	OPPTS 870.1300	
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)						
	oral	LD50	64 mg/kg	Rat	Manufacturer		
	dermal	LD50 mg/kg	92,4	Rabbit	Manufacturer		
	inhalation vapour	ATE	0,5 mg/l				
	inhalation (4 h) dust/mist	LC50 mg/l	0,171	Rat	Manufacturer	OECD 403	

Irritation and corrosivity

according to UK REACH Regulation

## MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 9 of 13

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Result / Evaluation: non-irritant. (Rabbit)

Method: OECD 404

Test was carried out with a similar formulation. (By analogy.)

Serious eye damage/eye irritation:

Result / Evaluation: non-irritant. (Rabbit)

Method: OECD 405

Test was carried out with a similar formulation. (By analogy.)

#### Sensitising effects

Based on available data, the classification criteria are not met.

Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of

5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Information on likely routes of exposure

Skin contact, Eye contact, @ES04.B002063, Inhalation.

## 11.2. Information on other hazards

### **Endocrine disrupting properties**

No information available.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 10 of 13

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
2634-33-5	1,2-benzisothiazol-3(2H)-	one; 1,2-bei	nzisothiazolin	-3-one			
	Acute algae toxicity	ErC50 mg/l	0,110	72 h	Selenastrum capricornutum	Manufacturer	OECD 201
	Acute crustacea toxicity	EC50 mg/l	0,643	48 h	Daphnia magna (Big water flea)	Manufacturer	OECD 202
	Fish toxicity	NOEC mg/l	0,21	28 d	Oncorhynchus mykiss (Rainbow trout)	Manufacturer	OECD 215
	Crustacea toxicity	NOEC mg/l	0,25	4 d	Mysidopsis bahia	Manufacturer	
	Acute bacteria toxicity	EC50	23 mg/l (	3 h	Activated sludge	Manufacturer	OECD 209
55965-84-9	reaction mass of 5-chloro	-2-methyl-2l	H-isothiazol-3	3-one and	d 2-methyl-2H-isothiazol-	3-one (3:1)	
	Acute algae toxicity	ErC50 mg/l	0,0052	72 h	Skeletonema costatum	Manufacturer	OECD 201
	Acute bacteria toxicity	EC50 mg/l ( )	7,92	3 h	Activated sludge	Manufacturer	OECD 209

## 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one					
	OECD 301C	85 %	63	Manufacturer		
	Moderately/partially biodegradable.					

# 12.3. Bioaccumulative potential

The product has not been tested.

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	-0,71 - 0,75

### BCF

CAS No	Chemical name	BCF	Species	Source
2634-33-5	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	6,62	Lepomis macrochirus (Bluegill)	Manufacturer
55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	3,6		Manufacturer

# 12.4. Mobility in soil

The product has not been tested.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No information available.

according to UK REACH Regulation

## MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 11 of 13

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

### **SECTION 14: Transport information**

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

### Inland waterways transport (ADN)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

# 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

Directive 2004/42/EC on VOC in

< 12 %

paints and varnishes:

### according to UK REACH Regulation

# MIXOL® Nr. 4 Oxyd-Rot

Revision date: 03.04.2024 Product code: PES55 Page 12 of 13

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

## 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

## Abbreviations and acronyms

Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Skin Sens: Skin sensitisation
Aquatic Acute: Acute aquatic hazard

Aquatic Acute: Acute aquatic nazard
Aquatic Chronic: Chronic aquatic hazard
CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

**UN: United Nations** 

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

according to UK REACH Regulation

	MIXOL® Nr. 4 Oxyd-Rot	
Revision date: 03.04.2024	Product code: PES55	Page 13 of 13

# Relevant H and EUH statements (number and full text)

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5 -chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

## **Further Information**

EUH210

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety data sheet available on request.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)